

View Online at <https://aerobasegroup.com/nsn/4320-00-854-3664>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Dust-ignition proof

**Pump Quantity:**

1

**Pumping Element Type:**

Piston

**Maximum Discharge Flow Rate:**

0.5 gallons per minute

**Discharge Pressure:**

7.2 pounds per square inch gage

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

0.4

**Discharge Connection Thread Size And Series/type Designator:**

0.125-27 nptf

**Intake Connection Thread Size And Series/type Designator:**

0.125-27 nptf

**Voltage In Volts:**

24.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400