NSN 4320-00-871-2314

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-00-871-2314

Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Media For Which Designed:
Hydrocarbon fuels and oils
Maximum Discharge Flow Rate:
51.0 gallons per minute
Discharge Pressure:
2000.0 pounds per square inch gage
Operating Speed At Rated Capacity:
2400.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Clockwise
Rotary Pump Design:
Rotary Pump Design: Gear
Gear
Gear Operation Method:
Gear Operation Method: Powered
Gear Operation Method: Powered Drive Shaft Type:
Gear Operation Method: Powered Drive Shaft Type: Splined, involute external
Gear Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator:
Gear Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator:
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt Special Features:
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt Special Features: 2 pumps in tandem
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt Special Features: 2 pumps in tandem Shelf Life:
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt Special Features: 2 pumps in tandem Shelf Life: N/a
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt Special Features: 2 pumps in tandem Shelf Life: N/a Unit Of Measure:
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt Special Features: 2 pumps in tandem Shelf Life: N/a Unit Of Measure:
Operation Method: Powered Drive Shaft Type: Splined, involute external Discharge Connection Thread Size And Series/type Designator: 1.250-11-1/2 npt Intake Connection Thread Size And Series/type Designator: 1.500-11-1/2 npt Special Features: 2 pumps in tandem Shelf Life: N/a Unit Of Measure: Demilitarization: