

View Online at <https://aerobasegroup.com/nsn/4320-00-872-9854>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

6.000 gallons per minute

**Discharge Pressure:**

200.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1425.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Prime Mover Power Rating:**

0.333 horsepower

**Voltage In Volts:**

220.0

**Phase:**

Single

**Frequency In Hertz:**

50.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400