

View Online at <https://aerobasegroup.com/nsn/4320-00-877-5379>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

19

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

85.0 gallons per minute

**Total Head:**

339.000 feet

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

19

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

4.000-8 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

25.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400