NSN 4320-00-877-6910

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-877-6910 **Thread Direction:** Right-hand **Torque Load Rating:** 453.0 inch-pounds **Spline Minor Diameter:** 0.550 inches **Spline Major Diameter:** 0.650 inches **Mounting Type:** Flange **Spline Quantity:** 12 **Mounting Hole Diameter:** 0.344 inches **Mounting Hole Quantity: Thread Size:** 1-1/16-12 **Operating Speed At Rated Capacity In Rpm:** 7000.0 **Drive Shaft Type:** Splined, straight external **Housing Material:** Steel **Screw Thread Series Designator:** Un **Shaft Rotation Direction:** Clockwise and counterclockwise **Thread Location:** Internal **Shaft Protrusion Length:** 1.130 inches **Connection Quantity:** 1 **Connection Type:** Inlet and outlet **Maximum Working Pressure Rating At Specificationified Tempurature Range:** 3000 psi at minus 35 degrees f to plus 275 degrees f **Connection Design:** Threaded

Spline Length:

0.820 inches

NSN 4320-00-877-6910 Hydraulic Motor - Page 2 of 2



Orive Shaft Government Standard:
None
Mounting Government Standard:
And10261-type x1
Displacement Type:
Constant
Constant Displacement Per Revolution:
0.950 cubic inches
Connection Government Specification/std:
And 10050-12
Mounting Bolt Hole Spacing:
Mtg holes spaced on 3.536 in. By 3.536 in.
Sc Application Data:
Handling and servicing equipment, guided missile
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
Г103-f