

View Online at <https://aerobasegroup.com/nsn/4320-00-888-9835>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dust-ignition proof

Pump Quantity:

1

Pumping Element Type:

Piston

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

4.6 gallons per minute

Discharge Pressure:

2700.0 pounds per square inch gage

Operating Speed At Rated Capacity:

5500.0 revolutions per minute

Pump Reciprocating Design:

Double acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Hydraulic cylinder

Control Location:

Center

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

32.0

Discharge Connection Thread Size And Series/type Designator:

0.562-18 unf

Intake Connection Thread Size And Series/type Designator:

0.875-14 unf

Prime Mover Power Rating:

8.500 horsepower

Voltage In Volts:

205.0

Special Features:

Elapsed time indicator

Frequency In Hertz:

400.0

Reference Number Differentiating Characteristics:

As differentiated by boeing source control ref 10-30422-1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A19400