

View Online at <https://aerobasegroup.com/nsn/4320-00-889-1571>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, salt

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Water cooled

Maximum Discharge Flow Rate:

600.0 gallons per minute

Total Head:

78.400 feet

Operating Speed At Rated Capacity:

1760.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

26.0

Features Provided:

Self-priming

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

W/electro dynamics motor dwg no. D79-943-3701406 08-501-388

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400