

View Online at <https://aerobasegroup.com/nsn/4320-00-889-7387>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Oil

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

15.0 gallons per minute

Discharge Pressure:

25.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Screw

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

4.5

Prime Mover Power Rating:

3.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

3 type and 0-1 class

Reference Number Differentiating Characteristics:

As differentiated by ac motor data

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400