

View Online at <https://aerobasegroup.com/nsn/4320-00-903-8632>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Dc

**Media For Which Designed:**

Oil

**Environmental Protection:**

Splash proof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

10.0 gallons per minute

**Discharge Pressure:**

10.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Screw

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

2.9

**Prime Mover Power Rating:**

1.000 horsepower

**Voltage In Volts:**

250.0

**Reference Number Differentiating Characteristics:**

As differentiated by general electric dc motor w/out repair parts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400