NSN 4320-00-904-3968

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-904-3968

| Prime Mover Quantity: |
|--|
| 1 |
| Mounting Type: |
| Wheel |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Media For Which Designed: |
| Water, fresh |
| Pump Quantity: |
| 1 |
| Maximum Discharge Flow Rate: |
| 600.0 gallons per minute |
| Total Head: |
| 50.000 feet |
| Suction Lift: |
| 10.000 feet |
| Operating Speed At Rated Capacity: |
| 3200.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Radial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Prime Mover Type: |
| Gasoline engine |
| Discharge Connection Thread Size And Series/type Designator: |
| 4.000-8 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 4.000-8 npt |
| Features Provided: |
| Self-priming |

NSN 4320-00-904-3968

Centrifugal Pump Unit - Page 2 of 2



| Prime Mover Power Rating: |
|----------------------------------|
| 20.000 horsepower |
| Specification Or Standard: |
| 2 type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A19400