

View Online at <https://aerobasegroup.com/nsn/4320-00-908-3761>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Wheel

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

20.0 gallons per minute

Discharge Pressure:

20.0 pounds per square inch gage

Total Head:

12.000 feet

Operating Speed At Rated Capacity:

1800.0 revolutions per minute

Rotary Pump Design:

Vane

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.5

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Prime Mover Power Rating:

0.750 horsepower

Voltage In Volts:

28.0

Special Features:

Designed for foam forming liquids, fire extinguishing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400