

View Online at <https://aerobasegroup.com/nsn/4320-00-915-3178>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Water, fresh

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Cooling Method:**

Water cooled

**Maximum Discharge Flow Rate:**

250.0 gallons per minute

**Total Head:**

100.000 feet

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

3.000-8 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

5.000 horsepower

**Voltage In Volts:**

230.0

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400