NSN 4320-00-929-5497

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-929-5497

| Torque Load Rating: |
|---|
| 114.0 inch-pounds |
| Spline Minor Diameter: |
| 0.375 inches |
| Spline Major Diameter: |
| Between 0.495 inches and 0.500 inches |
| Mounting Type: |
| Flange |
| Spline Quantity: |
| 11 |
| Mounting Hole Diameter: |
| 0.250 inches |
| Mounting Hole Quantity: |
| 4 |
| Bolt Hole Quantity: |
| 4 and 4 |
| Operating Speed At Rated Capacity In Rpm: |
| 2400.0 |
| Pitch Diameter: |
| 0.458 inches |
| Drive Shaft Type: |
| Splined, involute external |
| Housing Material: |
| Steel |
| Shaft Rotation Direction: |
| Clockwise |
| Shaft Protrusion Length: |
| 0.665 inches |
| Spline Pitch: |
| 24/48 |
| Connection Quantity: |
| 1 and 1 |
| Connection Type: |
| Inlet and outlet |
| Connection Design: |
| Flanged and threaded |
| Bolt Hole Thread Size: |
| 0.312-18 and 0.312-18 |
| Spline Pressure Angle In Deg: |
| 30.0 |
| Spline Length: |
| 0.580 inches |

NSN 4320-00-929-5497 Hydraulic Motor - Page 2 of 2



| Displacement Type: |
|---------------------------------------|
| Constant |
| Constant Displacement Per Revolution: |
| 0.310 cubic inches |
| Bolt Hole Spacing: |
| 1.500 in. By 0.688 in. |
| Mounting Bolt Hole Spacing: |
| 3.250 in. By 2.687 in. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

T103-f