NSN 4320-00-933-6551

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-933-6551

Prime Mover Quantity: 1 Prime Mover Cooling Medium: Air Stage Quantity: 1 Intake Connection Quantity: 1 Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	
Prime Mover Cooling Medium: Air Stage Quantity: Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: IDischarge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Prime Mover Quantity:
Stage Quantity: Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	1
Stage Quantity: Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Prime Mover Cooling Medium:
Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Air
Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Stage Quantity:
Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	1
Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Intake Connection Quantity:
Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	1
Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Intake Connection Type:
Discharge Connection Type: Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Round flange
Round flange Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Discharge Connection Quantity:
Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	1
Current Type: Ac Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Discharge Connection Type:
Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Round flange
Media For Which Designed: Water, fresh Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Current Type:
Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Ac
Environmental Protection: Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Media For Which Designed:
Splash proof Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Water, fresh
Pump Quantity: 1 Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Environmental Protection:
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Splash proof
Cooling Method: Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Pump Quantity:
Self ventilated Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	1
Maximum Discharge Flow Rate: 13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Cooling Method:
13.0 gallons per minute Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Self ventilated
Total Head: 158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Maximum Discharge Flow Rate:
158.000 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	13.0 gallons per minute
Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Total Head:
3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	158.000 feet
Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Operating Speed At Rated Capacity:
Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	3500.0 revolutions per minute
Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Pumping Element Operating Position:
Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Horizontal
Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Centrifugal Pump Design:
1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	
1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Electric motor Inclosure Type:	Centrifugal Pump Impeller Quantity:
Single Prime Mover Type: Electric motor Inclosure Type:	
Prime Mover Type: Electric motor Inclosure Type:	Centrifugal Pump Impeller Suction Type:
Electric motor Inclosure Type:	Single
Electric motor Inclosure Type:	·
	Inclosure Type:
Fully enclosed	Fully enclosed
- "	Single Prime Mover Type: Electric motor Inclosure Type:

NSN 4320-00-933-6551

Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:
7.5
Features Provided:
Self-priming
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400