
# NSN 4320-00-934-7901

Centrifugal Pump Unit - Page 1 of 2





Prime Mover Quantity:

1

Stage Quantity:

1

## Intake Connection Quantity:

1

### Intake Connection Type:

Threaded internal

#### **Discharge Connection Quantity:**

1

#### **Discharge Connection Type:**

Threaded internal

#### **Current Type:**

Ac/dc

### Media For Which Designed:

## Water, fresh

Pump Quantity:

1

## Maximum Discharge Flow Rate:

12.0 gallons per minute

#### **Discharge Pressure:**

25.0 pounds per square inch gage

## Pumping Element Operating Position:

Horizontal

## **Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:** 

1

## Centrifugal Pump Impeller Suction Type:

Single

#### Prime Mover Type:

Electric motor

#### Inclosure Type:

Fully enclosed

## Discharge Connection Thread Size And Series/type Designator:

1.062-12 un

#### Intake Connection Thread Size And Series/type Designator:

1.312-12 un

## **Features Provided:**

Self-priming

#### Voltage In Volts:

120.0 and 208.0

# NSN 4320-00-934-7901

Centrifugal Pump Unit - Page 2 of 2

Phase:

Three

Frequency In Hertz:

400.0

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A19400

