NSN 4320-00-936-3977

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-00-936-3977

Intake Connection Type: Rectangular flange Discharge Connection Quantity: 1 Discharge Connection Type: Rectangular flange Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A19400	Intake Connection Quantity:
Discharge Connection Quantity: 1 Discharge Connection Type: Rectangular flange Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1
Discharge Connection Quantity: 1 Discharge Connection Type: Rectangular flange Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Intake Connection Type:
Discharge Connection Type: Rectangular flange Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rectangular flange
Discharge Connection Type: Rectangular flange Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Discharge Connection Quantity:
Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1
Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Discharge Connection Type:
Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rectangular flange
Maximum Discharge Flow Rate: 57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Media For Which Designed:
57.0 gallons per minute Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hydrocarbon fuels and oils
Discharge Pressure: 3000.0 pounds per square inch gage Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Maximum Discharge Flow Rate:
Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	57.0 gallons per minute
Operating Speed At Rated Capacity: 2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Discharge Pressure:
2500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3000.0 pounds per square inch gage
Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Operating Speed At Rated Capacity:
Horizontal Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2500.0 revolutions per minute
Pump Rotation Direction: Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Pumping Element Operating Position:
Clockwise Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Horizontal
Rotary Pump Design: Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Pump Rotation Direction:
Vane Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Clockwise
Operation Method: Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rotary Pump Design:
Powered Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Vane
Features Provided: Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Operation Method:
Integral relief valve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Powered
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Features Provided:
N/a Unit Of Measure: Demilitarization: No Fiig:	Integral relief valve
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
	Fiig:
1119 199	A19400