NSN 4320-00-937-6725

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-937-6725

Stage Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded internal Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	Prime Mover Quantity:
Stage Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded internal Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Discharge Connection Quantity: Discharge Connection Type: Threaded internal Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Discharge Connection Quantity: 1 Discharge Connection Type: Threaded internal Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Discharge Connection Type: Threaded internal Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Discharge Connection Type: Threaded internal Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Threaded internal Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Media For Which Designed: Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Sewage Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Power Drive Operating Pressure: 80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
80.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	·
Pump Quantity: 1 Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Maximum Discharge Flow Rate: 210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
210.0 gallons per minute Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Total Head: 25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
25.000 feet Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Operating Speed At Rated Capacity: 2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
2900.0 revolutions per minute Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Pumping Element Operating Position: Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Vertical Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	Centrifugal Pump Impeller Quantity:
Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Single Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	Centrifugal Pump Impeller Suction Type:
Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	·
2.500-8 npt Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	
Features Provided: Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	Discharge Connection Thread Size And Series/type Designator:
Self-priming Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	2.500-8 npt
Prime Mover Power Rating: 5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	Features Provided:
5.000 horsepower Specification Or Standard: 1 class Shelf Life: N/a	Self-priming
Specification Or Standard: 1 class Shelf Life: N/a	Prime Mover Power Rating:
1 class Shelf Life: N/a	5.000 horsepower
Shelf Life: N/a	Specification Or Standard:
N/a	1 class
	Shelf Life:
	N/a
Unit Of Measure:	Unit Of Measure:

NSN 4320-00-937-6725

Centrifugal Pump Unit - Page 2 of 2



Demilitarization:

No

Fiig:

A19400