

View Online at <https://aerobasegroup.com/nsn/4320-00-944-6143>

Mounting Type:

Skid mtd

Discharge Connection Flange Thickness:

1.000 inches

Prime Mover Type:

Diesel engine

Discharge Connection Type:

Flanged

Capacity Rating:

600.0 gallons per minute

Suction Connection Type:

Flanged

Pump Type:

Centrifugal

Suction Connection Flange Type:

Drilled

Suction Connection Flange Thickness:

1.000 inches

Suction Connection Flange Bolt Circle Diameter:

9.500 inches

Suction Connection Flange Bolt Hole Quantity:

8

Suction Connection Flange Bolt Hole Diameter:

0.812 inches

Discharge Connection Flange Bolt Circle Diameter:

9.5000 inches

Discharge Connection Flange Bolt Hole Quantity:

8

Discharge Connection Flange Bolt Hole Diameter:

0.812 inches

Explosion Proof Feature:

Not included

Discharge Connection Flange Type:

Drilled

Hose Type:

Suction

Hose Section Quantity:

4

Hose Length:

20.000 feet

Hose Inside Diameter:

6.000 inches

Ground Cable:

Included

Cable Reel:

Not included

Drum Emptying Manifold Assembly:

Not included

Specification Or Standard:

3 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T103-m