

View Online at <https://aerobasegroup.com/nsn/4320-00-949-6842>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Hydrocarbon fuels and oils

**Cylinder Quantity:**

9

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Pump Quantity:**

1

**Pumping Element Type:**

Piston

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

6.0 gallons per minute

**Discharge Pressure:**

3000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

3200.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Pressure compensation

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.875-14 unf

**Intake Connection Thread Size And Series/type Designator:**

1.062-12 un

**Prime Mover Power Rating:**

10.250 horsepower

**Voltage In Volts:**

222.0

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A19400