

View Online at <https://aerobasegroup.com/nsn/4320-00-952-8645>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal and threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal and threaded external

Current Type:

Ac

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

6.5 gallons per minute

Total Head:

30.000 feet

Suction Lift:

5.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

0.750-14 npt and 0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.750-14 npt and 0.375-18 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.100 horsepower

Voltage In Volts:

110.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400