## NSN 4320-00-953-8063

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-953-8063

Thread Direction:
Right-hand
Torque Load Rating:
270.0 inch-pounds
Mounting Type:
Flange
Keyway Width:
0.188 inches
Keyway Depth:
0.094 inches
Mounting Hole Diameter:
0.287 inches
Mounting Hole Quantity:
4
Thread Size:
1.062-12 and 0.438-20
Shaft Diameter:
0.749 inches
Operating Speed At Rated Capacity In Rpm:
3600.0
Keyway Length:
0.718 inches
Drive Shaft Type:
Machine keyway
Housing Material:
Steel
Screw Thread Series Designator:
Unf
Shaft Rotation Direction:
Clockwise and counterclockwise
Thread Location:
Internal
Shaft Protrusion Length:
1.531 inches
Connection Quantity:
1
Connection Type:
Inlet and drain
Maximum Working Pressure Rating At Specificationified Tempurature Range:
3000 psi at minus 65 degrees f to plus 160 degrees f
Connection Design:
Threaded

## **NSN 4320-00-953-8063** Hydraulic Motor - Page 2 of 2



Displacement Type:
Constant
Constant Displacement Per Revolution:
0.643 cubic inches
Mounting Bolt Hole Spacing:
1.687 in. By 3.437 in. C to c
Housing Surface Treatment:
Enameled
Fsc Application Data:
Truck, lift, munitions handling loading
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T103-f