# NSN 4320-00-953-8063

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-953-8063

Thread Direction:

Right-hand

**Torque Load Rating:** 

270.0 inch-pounds

# Mounting Type:

Flange

# Keyway Width:

0.188 inches

Keyway Depth:

0.094 inches

Mounting Hole Diameter:

0.287 inches

#### Mounting Hole Quantity:

4

#### Thread Size:

1.062-12 and 0.438-20

Shaft Diameter:

0.749 inches

## Operating Speed At Rated Capacity In Rpm:

3600.0

# Keyway Length:

0.718 inches

### Drive Shaft Type:

Machine keyway

#### Housing Material:

Steel

# Screw Thread Series Designator:

Unf

#### Shaft Rotation Direction:

Clockwise and counterclockwise

#### **Thread Location:**

Internal

# Shaft Protrusion Length:

1.531 inches

# **Connection Quantity:**

1

# Connection Type:

Inlet and drain

### Maximum Working Pressure Rating At Specificationified Tempurature Range:

3000 psi at minus 65 degrees f to plus 160 degrees f

# **Connection Design:**

Threaded

# NSN 4320-00-953-8063

Hydraulic Motor - Page 2 of 2



Displacement Type: Constant **Constant Displacement Per Revolution:** 0.643 cubic inches Mounting Bolt Hole Spacing: 1.687 in. By 3.437 in. C to c Housing Surface Treatment: Enameled **Fsc Application Data:** Truck, lift, munitions handling loading Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T103-f