NSN 4320-00-955-3126

Reciprocating Pump - Page 1 of 2





Mounting Type:

Base

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Spur gear

Media For Which Designed:

Hydrocarbon fuels and oils

Pumping Element Type:

Piston

Maximum Discharge Flow Rate:

6.0 gallons per minute

Discharge Pressure:

3000.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3000.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Hydraulic cylinder

Control Location:

Center

Operation Method:

Powered

Drive Shaft Type:

Splined, straight external

Drive Shaft End Diameter:

0.867 inches

Drive Shaft Length:

0.543 inches

NSN 4320-00-955-3126

Reciprocating Pump - Page 2 of 2



Discharge Connection Thread Size And Series/type Designator:

0.875-14 unf

Intake Connection Thread Size And Series/type Designator:

1.312-12 un

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A19400