

View Online at <https://aerobasegroup.com/nsn/4320-00-958-4402>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Trailer

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

60.0 gallons per minute

**Discharge Pressure:**

50.0 pounds per square inch gage

**Total Head:**

20.000 feet

**Operating Speed At Rated Capacity:**

500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Prime Mover Power Rating:**

2.000 horsepower

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400