NSN 4320-00-958-4402

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-958-4402

| Prime Mover Quantity: |
|--|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Mounting Type: |
| Trailer |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Pump Quantity: |
| 1 |
| Maximum Discharge Flow Rate: |
| 60.0 gallons per minute |
| Discharge Pressure: |
| 50.0 pounds per square inch gage |
| Total Head: |
| 20.000 feet |
| Operating Speed At Rated Capacity: |
| 500.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Rotary Pump Design: |
| Gear |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Discharge Connection Thread Size And Series/type Designator: |
| 2.000-11-1/2 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 2.000-11-1/2 npt |
| Prime Mover Power Rating: |
| 2.000 horsepower |

NSN 4320-00-958-4402

Rotary Pump Unit - Page 2 of 2



| Voltage In Volts: |
|---------------------|
| 230.0 and 460.0 |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A19400