

View Online at <https://aerobasegroup.com/nsn/4320-00-983-8767>

**Mounting Type:**

Skid mtd

**Discharge Connection Flange Thickness:**

1.000 inches

**Prime Mover Type:**

Diesel engine

**Discharge Connection Type:**

Flanged

**Capacity Rating:**

600.0 gallons per minute

**Suction Connection Type:**

Flanged

**Pump Type:**

Centrifugal

**Suction Connection Flange Type:**

Drilled

**Suction Connection Flange Thickness:**

1.000 inches

**Suction Connection Flange Bolt Circle Diameter:**

9.500 inches

**Suction Connection Flange Bolt Hole Quantity:**

8

**Suction Connection Flange Bolt Hole Diameter:**

0.812 inches

**Discharge Connection Flange Bolt Circle Diameter:**

9.500 inches

**Discharge Connection Flange Bolt Hole Quantity:**

8

**Discharge Connection Flange Bolt Hole Diameter:**

0.812 inches

**Explosion Proof Feature:**

Not included

**Discharge Connection Flange Type:**

Drilled

**Hose Type:**

Suction

**Hose Section Quantity:**

4

**Hose Length:**

20.000 feet

**Hose Inside Diameter:**

6.000 inches

**Ground Cable:**

Included

**Cable Reel:**

Not included

**Drum Emptying Manifold Assembly:**

Not included

**Special Features:**

Self lubricating shaft seal, cast iron body bronze fitted, suction line strainer aluminum, suction gate valve aluminum, suction coupler quick disconnect 6inch female w/gasket, discharge pressure regulating valve 120psi aluminum, lever operated check valve aluminum, air eliminator aluminum, discharge gate valve aluminum, discharge coupler quick disconnect 6inch male

**Specification Or Standard:**

1 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-m