

View Online at <https://aerobasegroup.com/nsn/4320-00-986-7312>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal and threaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal and threaded external

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

9.5 gallons per minute

**Discharge Pressure:**

4.3 pounds per square inch gage

**Total Head:**

40.000 feet

**Operating Speed At Rated Capacity:**

1725.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Discharge Connection Thread Size And Series/type Designator:**

0.500-14 npt and 0.750-11-1/2 nh

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 npt and 0.750-11-1/2 nh

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.333 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400