NSN 4320-00-987-7484

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-987-7484

| Torque Load Rating: |
|--|
| 117.3 inch-pounds |
| Spline Minor Diameter: |
| Between 1.049 inches and 1.062 inches |
| Spline Major Diameter: |
| Between 1.247 inches and 1.248 inches |
| Mounting Type: |
| Flange |
| Spline Quantity: |
| 12 |
| Bolt Hole Quantity: |
| 8 |
| Pitch Diameter: |
| 1.167 inches |
| Drive Shaft Type: |
| Splined, involute external |
| Shaft Rotation Direction: |
| Clockwise and counterclockwise |
| Shaft Protrusion Length: |
| 2.000 inches |
| Spline Pitch: |
| 12/24 |
| Connection Quantity: |
| 2 |
| Connection Type: |
| Inlet |
| Maximum Working Pressure Rating At Specificationified Tempurature Range: |
| 2000psi at minus 65 degrees f to plus170 degrees f |
| Connection Design: |
| Flanged |
| Bolt Hole Thread Size: |
| 0.500-13 |
| Spline Pressure Angle In Deg: |
| 30.0 |
| Spline Length: |
| 1.875 inches |
| Displacement Type: |
| Constant |
| Bolt Hole Spacing: |
| 1-13/32 in. By 2-3/4 in. 2 places |
| Housing Surface Treatment: |

Enameled

NSN 4320-00-987-7484

Hydraulic Motor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T103-f