## NSN 4320-00-989-9786

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-989-9786 **Thread Direction:** Right-hand **Torque Load Rating:** 91.0 inch-pounds **Mounting Type:** Pad **Keyway Width:** 0.188 inches **Keyway Depth:** 0.204 inches **Mounting Hole Diameter:** 0.500 inches **Mounting Hole Quantity: Thread Size:** 0.500-14 **Shaft Diameter:** 0.750 inches **Operating Speed At Rated Capacity In Rpm:** 2200.0 **Keyway Length:** 0.875 inches **Drive Shaft Type:** Machine keyway **Housing Material:** Iron, cast **Screw Thread Series Designator: Shaft Rotation Direction:** Counterclockwise **Accessory Components And Quantity:** Key machine 1 **Thread Location:** Internal **Connection Quantity:** 

**Connection Type:** 

Inlet and outlet

**Maximum Working Pressure Rating At Specificationified Tempurature Range:** 

850 psi at minus 40 degrees f to plus 250 degrees f

**Connection Design:** 

Threaded and threaded

## **NSN 4320-00-989-9786** Hydraulic Motor - Page 2 of 2

T103-f



Displacement Type:
Constant
Constant Displacement Per Revolution:
0.675 cubic inches
Mounting Bolt Hole Spacing:
1.990 in.Min, 2.010 in. Maximum by 1.990 in. Min 2.010 in. Maximum c to c
Specification Or Standard:
Dwg no. C81-8-912
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: