

View Online at <https://aerobasegroup.com/nsn/4320-00-999-5363>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Explosion proof

Pump Quantity:

1

Pumping Element Type:

Piston

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

8.0 gallons per minute

Discharge Pressure:

2200.0 pounds per square inch gage

Operating Speed At Rated Capacity:

5770.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Hydraulic cylinder

Control Location:

Center

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

37.5

Discharge Connection Thread Size And Series/type Designator:

0.750-16 unf

Intake Connection Thread Size And Series/type Designator:

1.062-12 un

Prime Mover Power Rating:

12.400 horsepower

Voltage In Volts:

200.0

Phase:

Three

Frequency In Hertz:

400.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400