

View Online at <https://aerobasegroup.com/nsn/4320-01-003-2506>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Water-air cooled

Maximum Discharge Flow Rate:

45.8 gallons per minute

Total Head:

15.000 feet

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

8.0

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400