

View Online at <https://aerobasegroup.com/nsn/4320-01-005-8116>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Ethylene glycol

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Quick disconnect

Discharge Connection Quantity:

1

Discharge Connection Type:

Quick disconnect

Current Type:

Ac

Media For Which Designed:

Ethylene glycol

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

63.0 gallons per minute

Discharge Pressure:

173.0 pounds per square inch gage

Total Head:

340.000 feet

Operating Speed At Rated Capacity:

2400.0 revolutions per minute

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Features Provided:

Self-priming

Prime Mover Power Rating:

16.000 horsepower

Voltage In Volts:

115.0 and 200.0

Phase:

Three

Frequency In Hertz:

400.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400