

View Online at <https://aerobasegroup.com/nsn/4320-01-009-4055>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Cylinder Quantity:**

7

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Environmental Protection:**

Explosion proof

**Pump Quantity:**

1

**Pumping Element Type:**

Piston

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

3.0 gallons per minute

**Discharge Pressure:**

2700.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

4500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Pressure compensation

**Control Location:**

Center

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.750-16 unf

**Intake Connection Thread Size And Series/type Designator:**

0.875-14 unf

**Prime Mover Power Rating:**

7.0 horsepower

**Voltage In Volts:**

115.0 and 200.0

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A19400