NSN 4320-01-011-6822

Hydraulic Motor - Page 1 of 2

Thread Direction:

Right-hand



View Online at https://aerobasegroup.com/nsn/4320-01-011-6822

Torque Load Rating:
60.96 centimeter-kilograms
Mounting Type:
Flange
Mounting Hole Diameter:
14.3 millimeters
Mounting Hole Quantity:
2
Thread Size:
0.250 and 1.000-11-1/2 and 1.000-11-1/2
Shaft Diameter:
22.2 millimeters
Operating Speed At Rated Capacity In Rpm:
3000.0
Mounting Bolt Circle Diameter:
146.5 millimeters
Drive Shaft Type:
Woodruff keyway
Screw Thread Series Designator:
Nptf
Shaft Rotation Direction:
Clockwise and counterclockwise
Distance From End To Keyway Center:
11.1 millimeters
11.1 millimeters Thread Location:
Thread Location:
Thread Location: Internal
Thread Location: Internal Shaft Protrusion Length:
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity:
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1 Connection Type:
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1 Connection Type: Drain and inlet and outlet
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1 Connection Type: Drain and inlet and outlet Maximum Working Pressure Rating At Specificationified Tempurature Range:
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1 Connection Type: Drain and inlet and outlet Maximum Working Pressure Rating At Specificationified Tempurature Range: 210 bar at minus 40 degrees c to plus 82 degrees c
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1 Connection Type: Drain and inlet and outlet Maximum Working Pressure Rating At Specificationified Tempurature Range: 210 bar at minus 40 degrees c to plus 82 degrees c Connection Design:
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1 Connection Type: Drain and inlet and outlet Maximum Working Pressure Rating At Specificationified Tempurature Range: 210 bar at minus 40 degrees c to plus 82 degrees c Connection Design: Threaded
Thread Location: Internal Shaft Protrusion Length: 31.8 millimeters Connection Quantity: 2 and 1 and 1 Connection Type: Drain and inlet and outlet Maximum Working Pressure Rating At Specificationified Tempurature Range: 210 bar at minus 40 degrees c to plus 82 degrees c Connection Design: Threaded Sae Key Size Accommodated:

NSN 4320-01-011-6822 Hydraulic Motor - Page 2 of 2



Constant Displacement Per Revolution:
55.6 cubic centimeters
Mounting Bolt Hole Spacing:
Equally spaced
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T103-f