

View Online at <https://aerobasegroup.com/nsn/4320-01-012-5025>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Splash proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Discharge Pressure:

80.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.0

Discharge Connection Thread Size And Series/type Designator:

0.562-18 unf

Intake Connection Thread Size And Series/type Designator:

0.562-18 unf

Prime Mover Power Rating:

0.250 horsepower

Voltage In Volts:

115.0

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by the source control dwg no.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400