

View Online at <https://aerobasegroup.com/nsn/4320-01-012-5025>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Splash proof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Discharge Pressure:**

80.0 pounds per square inch gage

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.0

**Discharge Connection Thread Size And Series/type Designator:**

0.562-18 unf

**Intake Connection Thread Size And Series/type Designator:**

0.562-18 unf

**Prime Mover Power Rating:**

0.250 horsepower

**Voltage In Volts:**

115.0

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by the source control dwg no.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400