

View Online at <https://aerobasegroup.com/nsn/4320-01-013-0798>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Wheel

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Pump Quantity:

1

Maximum Discharge Flow Rate:

400.0 gallons per minute

Total Head:

15.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Gasoline engine

Discharge Connection Thread Size And Series/type Designator:

3.000-8 npt

Intake Connection Thread Size And Series/type Designator:

3.000-8 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

9.500 horsepower

Special Features:

2 ea brass male adapter, pipe to hose, 1 cast iron ft valve strainer combination, 2 hose section 3 in. By 20 ft w/a male and female swivel brass coupling each, trash pump mt on pneumatic wheelbarrow tires, unit accomodates spherical solids up to 0.750 in. Dia

Specification Or Standard:

I type and 20m size and a material and 2 class and a style

Departure From Cited Document:

As differentiated by extra attachments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400