

View Online at <https://aerobasegroup.com/nsn/4320-01-013-9854>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Photographic developers

Pump Quantity:

1

Maximum Discharge Flow Rate:

15.0 gallons per minute

Total Head:

70.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

1.000 horsepower

Voltage In Volts:

230.0

Phase:

Three

Special Features:

Binitial instl request p/n 183-030 which includes p/n183-022 pumpunit, centrifugal and installation instructions p/n183-029.For pump and motor replacement only, order fscm 04579, p/n1x1-1/4x5type321

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400