

View Online at <https://aerobasegroup.com/nsn/4320-01-017-0822>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

50.0 gallons per minute

**Discharge Pressure:**

175.0 pounds per square inch gage

**Total Head:**

25.000 feet

**Suction Lift:**

10.000 feet

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Length:**

20.000 inches

**Unpackaged Unit Width:**

7.5000 inches

**Unpackaged Unit Height:**

12.500 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

1.250-11.500 npt

**Intake Connection Thread Size And Series/type Designator:**

1.250-11.500 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.250 horsepower

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400