## NSN 4320-01-018-1668

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-018-1668

| Thread Direction:  |
|--|
| Right-hand and right-hand  |
| Mounting Type:   |
| Flange   |
| Mounting Hole Quantity:  |
| 4  |
| Thread Size:   |
| 0.500-14 and 0.500-14  |
| Shaft Diameter:  |
| 1.000 inches   |
| Operating Speed At Rated Capacity In Rpm:                                |
| 182.0  |
| Mounting Bolt Circle Diameter:   |
| 3.250 inches   |
| Drive Shaft Type:  |
| Woodruff keyway  |
| Screw Thread Series Designator:  |
| Nptf and nptf  |
| Shaft Rotation Direction:  |
| Clockwise and counterclockwise   |
| Distance From End To Keyway Center:                                      |
| 0.730 inches   |
| Thread Location:   |
| Internal and internal  |
| Shaft Protrusion Length:   |
| 1.780 inches   |
| Connection Quantity:   |
| 1 and 1  |
| Connection Type:   |
| Inlet and outlet   |
| Maximum Working Pressure Rating At Specificationified Tempurature Range: |
| 900psi at 180 degrees f  |
| Connection Design:   |
| Threaded and threaded  |
| Sae Key Size Accommodated:   |
| 15   |
| Displacement Type:   |
| Variable   |
| Constant Displacement Per Revolution:                                    |
| 17.900 cubic inches  |
| Mounting Rolf Hole Spacing:  |

45.0 degrees apart

## NSN 4320-01-018-1668

Hydraulic Motor - Page 2 of 2



| Special | Features: |
|---------|-----------|
|---------|-----------|

Mtg holes 0.375-16 unc thd

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f