# NSN 4320-01-019-6132

Centrifugal Pump Unit - Page 1 of 2

Prime Mover Cooling Medium:

Air

Stage Quantity:





### 1 Intake Connection Quantity: 1 Intake Connection Type: Threaded internal **Discharge Connection Quantity:** 1 **Discharge Connection Type:** Threaded internal **Current Type:** Ac Media For Which Designed: Water, fresh **Environmental Protection:** Dripproof **Pump Quantity:** 1 **Cooling Method:** Self ventilated Maximum Discharge Flow Rate: 40.0 gallons per minute **Discharge Pressure:** 125.0 pounds per square inch gage **Total Head:** 11.000 feet **Operating Speed At Rated Capacity:** 1725.0 revolutions per minute **Centrifugal Pump Design:** Radial flow **Centrifugal Pump Impeller Quantity:** 1 **Centrifugal Pump Impeller Suction Type:** Single Prime Mover Type: Electric motor Inclosure Type: Open Voltage In Volts: 115.0

# NSN 4320-01-019-6132

Centrifugal Pump Unit - Page 2 of 2

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A19400

