

View Online at <https://aerobasegroup.com/nsn/4320-01-024-8178>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Ethylene glycol and water, distilled

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Water cooled

**Maximum Discharge Flow Rate:**

6.4 gallons per minute

**Discharge Pressure:**

130.0 pounds per square inch gage

**Total Head:**

230.000 feet

**Operating Speed At Rated Capacity:**

3420.0 revolutions per minute

**Volume Control Type:**

Rotary

**Control Location:**

Center

**Rotary Pump Design:**

Vane

**Operation Relationship Design:**

Independent

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

14.0

**Discharge Connection Thread Size And Series/type Designator:**

1.312-12 un

**Intake Connection Thread Size And Series/type Designator:**

1.312-12 un

**Prime Mover Power Rating:**

2.000 horsepower

**Voltage In Volts:**

115.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400