

View Online at <https://aerobasegroup.com/nsn/4320-01-024-8178>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Ethylene glycol and water, distilled

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Water cooled

Maximum Discharge Flow Rate:

6.4 gallons per minute

Discharge Pressure:

130.0 pounds per square inch gage

Total Head:

230.000 feet

Operating Speed At Rated Capacity:

3420.0 revolutions per minute

Volume Control Type:

Rotary

Control Location:

Center

Rotary Pump Design:

Vane

Operation Relationship Design:

Independent

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

14.0

Discharge Connection Thread Size And Series/type Designator:

1.312-12 un

Intake Connection Thread Size And Series/type Designator:

1.312-12 un

Prime Mover Power Rating:

2.000 horsepower

Voltage In Volts:

115.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400