

View Online at <https://aerobasegroup.com/nsn/4320-01-024-8642>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

3.0 gallons per minute

Total Head:

13.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

2.1

Prime Mover Power Rating:

0.020 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400