

View Online at <https://aerobasegroup.com/nsn/4320-01-027-0193>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Pump Quantity:

1

Pumping Element Type:

Piston

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

26.0 gallons per minute

Discharge Pressure:

14.0 pounds per square inch gage

Total Head:

110.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Fixed

Control Location:

Right side

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.5 and 5.0

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

0.750-14 npt

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

Non-self priming

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400