

View Online at <https://aerobasegroup.com/nsn/4320-01-027-0193>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Pump Quantity:**

1

**Pumping Element Type:**

Piston

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

26.0 gallons per minute

**Discharge Pressure:**

14.0 pounds per square inch gage

**Total Head:**

110.000 feet

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Fixed

**Control Location:**

Right side

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

2.5 and 5.0

**Discharge Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Intake Connection Thread Size And Series/type Designator:**

0.750-14 npt

**Prime Mover Power Rating:**

0.333 horsepower

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Special Features:**

Non-self priming

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400