# NSN 4320-01-028-3610

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-028-3610

#### **Thread Direction:**

Right-hand and right-hand

## **Torque Load Rating:**

10000.0 inch-pounds

# Mounting Type:

Face

### Keyway Width:

0.500 inches

#### Keyway Depth:

0.250 inches

#### Mounting Hole Diameter:

0.375 inches

## Mounting Hole Quantity:

6

#### Thread Size:

0.875-14 and 0.875-14

## Shaft Diameter:

1.875 inches

## **Operating Speed At Rated Capacity In Rpm:**

150.0

# Mounting Bolt Circle Diameter:

6.000 inches

## Keyway Length:

2.625 inches

#### Drive Shaft Type:

Machine keyway

#### Screw Thread Series Designator:

Unf and unf

#### Shaft Rotation Direction:

Clockwise and counterclockwise

#### Thread Location:

Internal and internal

#### Shaft Protrusion Length:

3.000 inches

#### **Connection Quantity:**

1 and 1

### **Connection Type:**

Drain and outlet

#### Maximum Working Pressure Rating At Specificationified Tempurature Range:

2000psi at minus 40 degrees f to plus 160 degrees f

# **Connection Design:**

Threaded and threaded

# NSN 4320-01-028-3610

Hydraulic Motor - Page 2 of 2

Displacement Type:

Constant

# **Constant Displacement Per Revolution:**

34.800 cubic inches

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

T103-f

