

View Online at <https://aerobasegroup.com/nsn/4320-01-029-2786>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Wheel

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Pump Quantity:**

1

**Pumping Element Type:**

Diaphragm

**Maximum Discharge Flow Rate:**

100.0 gallons per minute

**Total Head:**

10.000 feet

**Suction Lift:**

10.000 feet

**Operating Speed At Rated Capacity:**

60.0 strokes per minute

**Pumping Element Operating Position:**

Vertical

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Fixed

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Gasoline engine

**Discharge Connection Thread Size And Series/type Designator:**

4.000-8 npt

**Intake Connection Thread Size And Series/type Designator:**

4.000-8 npt

**Special Features:**

2 brass male-pipe to hose adapters, 4 in., 1 cast iron foot valve strainer combination, 2 lengths of hose 4 in. By 20 ft w/a male and female swivel brass coupling affixed to each

**Specification Or Standard:**

1 class and b size

**Departure From Cited Document:**

As differentiated by special features as extra attachments

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400

**Mil-std (military Standard):**

Mil-p-509 spec.