

View Online at <https://aerobasegroup.com/nsn/4320-01-029-2786>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Wheel

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Maximum Discharge Flow Rate:

100.0 gallons per minute

Total Head:

10.000 feet

Suction Lift:

10.000 feet

Operating Speed At Rated Capacity:

60.0 strokes per minute

Pumping Element Operating Position:

Vertical

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Fixed

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Gasoline engine

Discharge Connection Thread Size And Series/type Designator:

4.000-8 npt

Intake Connection Thread Size And Series/type Designator:

4.000-8 npt

Special Features:

2 brass male-pipe to hose adapters, 4 in., 1 cast iron foot valve strainer combination, 2 lengths of hose 4 in. By 20 ft w/a male and female swivel brass coupling affixed to each

Specification Or Standard:

1 class and b size

Departure From Cited Document:

As differentiated by special features as extra attachments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400

Mil-std (military Standard):

Mil-p-509 spec.