

View Online at <https://aerobasegroup.com/nsn/4320-01-030-4361>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Water, fresh

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

1.0 gallons per minute

Discharge Pressure:

14.0 pounds per square inch gage

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.5

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Prime Mover Power Rating:

0.083 horsepower

Voltage In Volts:

27.0

Special Features:

W/braided tubular ground wire, 0.093 in. Od

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400